

## KENT SOLO CHEQUER KSCHQ-450/450


The Kent Solo Chequer manholes, KSCHQ-450/450, are solid top manholes with a raised 'chequer plate' surface. They are manufactured in accordance with BS EN124 and FACTA standards and are available in various loadings. They come manufactured from Grade 304L or Grade 316L Stainless Steel as standard and galvanised versions are available.

There is a Double Sealed version available and there is also an option to add an Inspection Port as a feature (150mm x 150mm hinged).

Manholes can be supplied with a powdercoated finish where there may be a need to increase the visibility of the manhole.

### Features


- ❑ Chequer Plate surface finish
- ❑ Lockdown feature available
- ❑ Shallow Tray Depth—20mm for light loading areas
- ❑ 4 Lifting points per cover



Product Code	Clear Opening	Tray Depth	Visible Frame Size (Unsealed)
KSCHQ-450/450	450mm x 450mm	50mm	550mm x 550mm
KSCHQ-600/450	600mm x 450mm	50mm	700mm x 550mm
KSCHQ-600/600	600mm x 600mm	50mm	700mm x 700mm
KSCHQ-750/600	750mm x 600mm	50mm	850mm x 700mm
KSCHQ-750/750	750mm x 750mm	50mm	850mm x 850mm
KSCHQ-900/600	900mm x 600mm	50mm	1000mm x 700mm
KSCHQ-900/750	900mm x 750mm	50mm	1000mm x 850mm
KSCHQ-900/900	900mm x 900mm	50mm	1000mm x 1000mm

**Specify: Kent Solo Chequer Manhole KSCHQ-450/450; 450mm x 450mm clear opening; Unsealed; 50mm Tray Depth; Grade 316L Stainless Steel; Loading FACTA B**  
 See page 8 & 9 which shows how to create your own unique specification clause

**Customised sizes to suit specific projects available in small production runs at no extra cost**



OPTIONS
Various Loadings (See BS EN124 and FACTA tables)
Grade 304L Stainless Steel
Grade 316L Stainless Steel
Mild Steel Galvanised (In accordance with BS EN ISO 1461 (1999))
Mild Steel Galvanised to 140 Micron (minimum requirement for Middle East projects)
Various Tray Depths (20mm, 50mm, 80mm, 100mm)
Lockdown
Unsealed or Double Sealed
Powdercoated finish

BSEN124	Slow Moving Wheel Loads	Kent Safety Test (Unfilled)
A15	0.6T	1.5T
B125	5.0T	12.5T
C250	6.5T	25.0T
D400	11.0T	40.0T

FACTA Class	Slow Moving Wheel Loads	Kent Safety Test (Unfilled)
A	0.6T	0.8T
AA	1.5T	3.1T
AAA	2.5T	5.2T
B	5T	10.1T
C	6.5T	13.2T
D	11T	22T